



1550 East Taylor Avenue
Atlanta, GA 30344
404-559-6000

FLEXAPOL LTMP 320

Synthetic Lubricant

FLEXAPOL LTMP 320 Advantages

- a. Superior lubricity for hydrodynamic lubrication at high speeds
 - i. Excellent Thermal Stability
- b. Low viscosity oil allows for good heat transfer;
- c. Compositional formulation provides for transparent finished products

Components

Tri-ester lubricant

Physical Properties

Appearance (30 deg. C)	:	Clear to light yellow / amber transparent liquid
Active content (100 – water %)	:	99+%
pH (5% Emulsion)	:	4.5 - 6
Brookfield Viscosity, cps	:	45 (nominal)
Color (Gardner)	:	2 max (nominal)
Density	:	0.79 (nominal)
Titer (°F)	:	not determined
Moisture % (KF)	:	1 max

Storage:

Please avoid high temperature and direct sun-light during the storage as physical properties affected by these factors. Shelf life of **Flexapol LTMP 320** is 12 months after production date in unopened containers (estimate).

Shipment:

This product is available in Drums, Totes or Bulk.



1550 East Taylor Avenue
Atlanta, GA 30344
404-559-6000

All suggestions and data are based on information and tests we believe to be reliable. Insofar as applications by prospective users may differ from those recommended, it is suggested the user conduct tests and determine the suitability of the product to his process. No warranty for the application of this product is expressed or implied. SSC Industries assumes no responsibility for personal injury or property damages to vendees, users or third parties caused by the material. Such vendees or users assume all risks.